

Technical data

ROTEX rotary motion speed	320 - 660 min ⁻¹
Eccentric motion speed	3 300 - 6 800 min ⁻¹
Sanding stroke	5 mm
FastFix sanding pad dia.	150 mm
Power consumption	720 W
Weight	2.3 kg
Dust extraction connection dia.	27 mm

Noise and vibration values

Polishing: Uncertainty (noise) K	3 dB
Polishing: Uncertainty (vibration) K	2.5 m/s ²
Polishing: A-weighted sound pressure level, LpA	82 dB(A)
Polishing: A-weighted sound power level, LWA	93 dB(A)
Polishing: Total vibration average, Ah	5 m/s ²
Polishing: Standards series EN 60745	
Fine sanding: Total vibration average, Ah	4 m/s ²
Fine sanding: Uncertainty (noise) K	3 dB
Fine sanding: Uncertainty (vibration) K	2 m/s ²
Fine sanding: A-weighted sound pressure level, LpA	82 dB(A)
Fine sanding: A-weighted sound power level, LWA	93 dB(A)
Fine sanding: Standards series EN 60745	
Coarse sanding: Uncertainty (vibration) K	2 m/s ²
Coarse sanding: A-weighted sound pressure level, LpA	82 dB(A)
Coarse sanding: Standards series EN 60745	
Coarse sanding: A-weighted sound power level, LWA	93 dB(A)
Coarse sanding: Uncertainty (noise) K	3 dB
Coarse sanding: Total vibration average, Ah	3.5 m/s ²