

## Technical data

Battery voltage	18 V
Gears	2
Idling speed, 1st gear/2nd gear	0 - 450/0 - 1500 min <sup>-1</sup>
Drilling diameter, wood/steel	45/13 mm
Torque adjustment 1st/2nd gear	0.8 - 8/0.5 - 6 Nm
Max. torque, wood/steel	35/50 Nm
Chuck range	1.5 - 13 mm
Li-ion battery capacity	3.1 Ah
Weight with Li-ion	1.5 kg

## Noise and vibration values

Drilling in metal: Standards series EN 60745	
Drilling in metal: Uncertainty (noise) K	3 dB
Drilling in metal: Uncertainty (vibration) K	1.5 m/s <sup>2</sup>
Drilling in metal: A-weighted sound pressure level, LpA	65 dB(A)
Drilling in metal: A-weighted sound power level, LWA	76 dB(A)
Fastening: Standards series EN 60745	
Fastening: Uncertainty (noise) K	3 dB
Fastening: Uncertainty (vibration) K	1.5 dB(A)
Fastening: A-weighted sound pressure level, LpA	65 dB(A)
Fastening: Total vibration average, Ah	2.5 m/s <sup>2</sup>
Fastening: A-weighted sound power level, LWA	76 dB(A)